

Product Series	Location		Mount Type				Airflow				Application						Drive Type		Impeller Type			Performance					
	outdoor	indoor	roof curb	base/floor	hanging	wall	ceiling	exhaust	supply	reversible	recirculate	general / clean air	contaminated air	spark resistant	grease (UL/cUL 705)	smoke control (UL)	high wind (150 mph)	high temp (200°F+)	seismic certification	belt	direct	centrifugal	propeller / axial	mixed flow	max CFM	max static pressure (in. wg)	
DUCT VENTILATION																											
IDL		✓		✓	✓			✓	✓			✓								✓		✓			5700	2.5	
IDB		✓		✓	✓			✓	✓			✓								✓		✓			5700	2.5	
IDB-X		✓		✓	✓			✓	✓			✓								✓		✓			5700	2.5	
SCT-IDB		✓		✓	✓			✓	✓			✓	✓							✓		✓			2000	2.5	
200		✓		✓	✓			✓	✓			✓								✓		✓			9600	2.5	
9200	✓			✓	✓			✓	✓			✓								✓		✓			13000	2.5	
9200-VIB	✓			✓	✓			✓	✓			✓								✓		✓			13000	2.5	
400		✓		✓	✓			✓	✓			✓								✓		✓			14300	2.5	
DSQ-B		✓		✓	✓			✓	✓			✓								✓		✓			14500	2	
GSQ-D		✓		✓	✓			✓	✓			✓								✓		✓			4200	1.5	
DPL		✓		✓				✓	✓			✓								✓		✓			30000	9	
DPL-AF		✓		✓				✓	✓			✓								✓		✓			20000	9	
DPL-DD		✓		✓				✓	✓			✓								✓		✓			30000	9	
IMF-B		✓		✓	✓			✓	✓			✓								✓			✓		43250	7.5	
BTA	✓	✓		✓	✓			✓	✓			✓								✓		✓			75110	1.5	
WTA	✓	✓		✓	✓			✓	✓			✓								✓		✓			75110	1.5	
HTA	✓	✓		✓	✓			✓	✓			✓								✓		✓			75110	1.5	
DDA	✓	✓		✓	✓			✓	✓			✓								✓		✓			53900	1.25	
JFHVA		✓		✓				✓				✓								✓		✓			29810	N/A	
CBF		✓					✓	✓				✓								✓		✓			1656	1	
L		✓					✓	✓				✓								✓		✓			704	1	
L-L		✓					✓	✓				✓								✓		✓			704	1	
SE		✓					✓	✓				✓								✓		✓			120	0.25	
SED		✓					✓	✓				✓								✓		✓			113	0.25	
CEP		✓					✓	✓				✓								✓		✓			140	0.25	
CEPD		✓					✓	✓				✓								✓		✓			200	0.25	
BPT		✓					✓	✓				✓								✓		✓			110	0.25	
DFRC-ES		✓		✓			✓	✓				✓								✓		✓			815	2.5	
AXC		✓		✓			✓	✓				✓								✓		✓			970	2	
VK		✓		✓			✓	✓				✓								✓		✓			871	1.5	
VK PS		✓		✓			✓	✓				✓								✓		✓			317	1.5	
VKM		✓		✓			✓	✓				✓								✓		✓			3096	2.5	
VKM-AR		✓		✓			✓	✓				✓								✓		✓			784	2.5	
TT		✓		✓			✓	✓				✓								✓			✓		1051	1.5	
TT PRO		✓		✓			✓	✓				✓								✓			✓		378	1	
TT SILENT		✓		✓			✓	✓				✓								✓			✓		327	1	
TT SILENT M		✓		✓			✓	✓				✓								✓			✓		1050	1	
VKP		✓		✓			✓	✓				✓								✓		✓			360	1	
VKOM		✓		✓			✓	✓				✓								✓		✓			262	0.25	

Product Series	Location		Mount Type				Airflow				Application						Drive Type		Impeller Type			Performance					
	outdoor	indoor	roof curb	base/floor	hanging	wall	ceiling	exhaust	supply	reversible	recirculate	general / clean air	contaminated air	spark resistant	grease (UL/cUL 705)	smoke control (UL)	high wind (150 mph)	high temp (200°F+)	seismic certification	belt	direct	centrifugal	propeller / axial	mixed flow	max CFM	max static pressure (in. wg)	
ERV / HRV																											
TWINFRESH RA1-50-2		✓				✓					✓										✓	✓				32	N/A
VENTO EXPERT A50-1 PRO		✓				✓					✓										✓	✓				29	N/A
MICRA 60		✓				✓					✓										✓	✓				35.3	N/A
MICRA 150		✓				✓					✓										✓	✓				71	N/A
GC30ERV-W		✓				✓					✓										✓	✓				32.7	N/A
ERV80-EC		✓			✓						✓										✓	✓				63	N/A
HRV 60S/120S		✓			✓						✓										✓	✓				155	1
ERV 60S/120S		✓			✓						✓										✓	✓				155	1
BRIG HRV		✓			✓						✓										✓	✓				257	1.4
ROOF MOUNT VENTILATION																											
HTE	✓		✓								✓										✓					7331	N/A
SIG	✓		✓								✓										✓					5200	2.5
SIS	✓		✓								✓										✓					12500	2.5
700	✓		✓								✓										✓					8500	2.5
9200 / 9200-VIB	✓		✓	✓							✓										✓					13000	2.5
300	✓		✓								✓										✓					8800	2.5
600	✓	✓	✓								✓										✓					14300	2.5
BI	✓	✓	✓								✓							✓			✓					27000	5
BI-RM	✓		✓								✓			✓				✓			✓					27000	5
HRE	✓		✓								✓			✓				✓			✓					12000	5
ALX-UD	✓	✓	✓			✓					✓			✓				✓			✓	✓				4300	2
ALX-DD	✓	✓	✓			✓					✓			✓				✓			✓	✓				4400	2
ALX-UB	✓	✓	✓			✓					✓			✓				✓			✓	✓				8600	2.25
ALX-DB	✓	✓	✓			✓					✓			✓				✓			✓	✓				8900	2.25
ALX-UD-EC	✓	✓	✓			✓					✓			✓				✓			✓	✓				4300	2
ALX-DD-EC	✓	✓	✓			✓					✓			✓				✓			✓	✓				4400	2
RTA	✓		✓								✓							✓			✓		✓			73090	1
RTA-SH	✓		✓								✓							✓			✓		✓			55520	1
RD	✓		✓								✓							✓			✓	✓				32564	0.375
RB	✓		✓								✓							✓			✓	✓				61562	0.375

Product Series	Location		Mount Type					Airflow					Application						Drive Type		Impeller Type			Performance			
	outdoor	indoor	roof curb	base/floor	hanging	wall	ceiling	exhaust	supply	reversible	recirculate	general / clean air	contaminated air	spark resistant	grease (UL/cUL 705)	smoke control (UL)	high wind (150 mph)	high temp (200°F+)	seismic certification	belt	direct	centrifugal	propeller / axial	mixed flow	max CFM	max static pressure (in. wg)	
WALL MOUNT VENTILATION																											
XBL		✓	✓			✓					✓									✓					21500	N/A	
XB		✓	✓			✓					✓									✓					49546	0.625	
SXB		✓	✓			✓					✓									✓					42114	0.625	
HV		✓	✓			✓					✓									✓					61149	0.75	
HVA		✓	✓			✓					✓									✓					75110	0.75	
ADD		✓	✓			✓					✓									✓					53900	1.25	
DDP		✓	✓			✓					✓									✓					9660	0.75	
DDS		✓	✓			✓					✓									✓					32563	0.75	
AX		✓				✓					✓									✓					14900	0.25	
AX-EC		✓				✓					✓									✓					10000	0.25	
AX-4		✓				✓					✓	✓	✓							✓					5520	0.25	
P		✓				✓					✓									✓					10000	0.25	
P-EC		✓				✓					✓									✓					10000	0.25	
P-4		✓				✓					✓	✓	✓							✓					5520	0.25	
SD		✓				✓					✓									✓					17200	0.25	
SD-EC		✓				✓					✓									✓					10000	0.25	
SD-XPF		✓				✓					✓	✓	✓							✓					5500	0.25	
XFS		✓				✓					✓									✓					10500	0.125	
GSF		✓				✓					✓									✓					6128	0.125	
ALX-UD	✓	✓	✓			✓					✓		✓							✓					4300	2	
ALX-DD	✓	✓	✓			✓					✓									✓					4400	2	
ALX-UB	✓	✓	✓			✓					✓		✓							✓					8600	2.25	
ALX-DB	✓	✓	✓			✓					✓								✓						8900	2.25	
ALX-UD-EC	✓	✓	✓			✓					✓		✓							✓					4300	2	
ALX-DD-EC	✓	✓	✓			✓					✓									✓					4400	2	
VCN	✓					✓					✓									✓					306	1.5	
OV1	✓					✓					✓									✓					766	0.375	
LD	✓					✓					✓									✓					109	0.03	
MA	✓					✓					✓									✓					176	0.03	
UTILITY, PRESSURE & RADIAL BLOWERS																											
BI	✓	✓		✓							✓								✓		✓				27000	5	
BI-RM	✓	✓		✓							✓		✓						✓		✓				27000	5	
400		✓		✓							✓								✓		✓				14300	2.5	
600		✓		✓							✓								✓		✓				14300	2.5	
PW		✓		✓							✓									✓		✓			2100	12	
KE		✓		✓							✓									✓		✓			3420	2.25	
D		✓		✓							✓									✓		✓			1970	2.25	
U		✓		✓							✓									✓			✓		9280	N/A	
PLASTEC	✓	✓	✓								✓	✓	✓							✓		✓			3750	5	
JET	✓	✓	✓								✓	✓	✓							✓		✓			2100	8.5	
STORM	✓	✓	✓								✓	✓	✓							✓		✓			1200	12	

Product Series	Location		Mount Type					Airflow					Application						Drive Type		Impeller Type			Performance			
	outdoor	indoor	roof curb	base/floor	hanging	wall	ceiling	exhaust	supply	reversible	recirculate	general / clean air	contaminated air	spark resistant	grease (UL/cUL 705)	smoke control (UL)	high wind (150 mph)	high temp (200°F+)	seismic certification	belt	direct	centrifugal	propeller / axial	mixed flow	max CFM	max static pressure (in. wg)	
GREEN PRODUCTS																											
200DD-EC		✓		✓	✓						✓									✓	✓				3600	1.25	
9200DD-EC	✓	✓		✓	✓						✓									✓	✓				3600	1.25	
GSQ-D-EC		✓		✓	✓						✓									✓	✓				4200	1.5	
300DD-EC	✓		✓								✓									✓	✓				3300	1.25	
SISDD-EC	✓		✓								✓									✓	✓				3300	1.25	
700DD-EC	✓		✓								✓									✓	✓				3800	1.5	
G-DDE		✓		✓							✓									✓	✓				3500	2	
SD-EC		✓				✓					✓									✓		✓			10000	0.25	
AX-EC		✓				✓					✓									✓		✓			10000	0.25	
P-EC		✓				✓					✓									✓		✓			10000	0.25	
OEM																											
G		✓		✓							✓									✓		✓			12500	2.5	
800		✓		✓							✓									✓		✓			18000	2.5	
900		✓		✓							✓									✓		✓			76000	2.5	
900-BI		✓		✓							✓									✓		✓			65000	5	
400		✓		✓							✓									✓		✓			14300	2.5	
DPL		✓		✓							✓									✓		✓			30000	9	
DPL-AF		✓		✓							✓									✓		✓			20000	9	
DPL-DL		✓		✓							✓										✓	✓			12000	5	
DPL-DC		✓		✓							✓										✓	✓			37600	11	
DPL-DP		✓		✓							✓										✓	✓			37700	13	
AIR CIRCULATION & MANCOOLERS																											
CJF		✓		✓		✓					✓									✓	✓				5378	N/A	
FANBOS		✓				✓			✓	✓	✓									✓		✓			N/A	N/A	
TRI-LITE		✓				✓			✓	✓	✓									✓		✓			N/A	N/A	
COMMERCIAL EC						✓			✓	✓	✓														N/A	N/A	
TRI-LITE		✓				✓			✓	✓	✓								✓			✓			N/A	N/A	
ECONOMIC						✓			✓	✓	✓									✓					N/A	N/A	
TRI-LITE DIRECT		✓				✓			✓	✓	✓									✓					N/A	N/A	
DRIVE		✓				✓			✓	✓	✓														N/A	N/A	
PENTA-LITE		✓				✓			✓	✓	✓										✓		✓		N/A	N/A	
COMMERCIAL EC						✓			✓	✓	✓														N/A	N/A	
PENTA-LITE		✓				✓			✓	✓	✓									✓			✓		N/A	N/A	
ECONOMIC						✓			✓	✓	✓														N/A	N/A	
HEXA-LITE		✓				✓			✓	✓	✓										✓		✓		N/A	N/A	
COMMERCIAL EC		✓				✓			✓	✓	✓									✓			✓		N/A	N/A	
ECONOMIC		✓				✓			✓	✓	✓									✓			✓		N/A	N/A	
OCTA-LITE		✓				✓			✓	✓	✓														N/A	N/A	
COMMERCIAL EC		✓				✓			✓	✓	✓										✓		✓		N/A	N/A	
CP-D (DC FANS)		✓				✓			✓	✓	✓										✓	✓			8944	N/A	
HVF		✓		✓					✓	✓	✓										✓	✓			5000	N/A	
HVRA		✓		✓					✓	✓	✓										✓	✓			12000	N/A	
LF		✓		✓					✓	✓	✓										✓	✓			5700	N/A	
HAF		✓		✓		✓			✓	✓	✓										✓	✓			3500	N/A	
CA		✓		✓		✓			✓	✓	✓										✓	✓			8300	N/A	
PBKD		✓		✓	✓				✓	✓	✓										✓	✓			8300	N/A	
WMKD		✓		✓	✓	✓			✓	✓	✓										✓	✓			8300	N/A	
CCU		✓		✓					✓	✓	✓										✓	✓			6200	N/A	