



## Low cost, dependable K-Kontrol Thermostats

### Features

- Single KJ16110, portable single KP16110 and two KT16110 stage models.
- Reliable Johnson thermostats, low cost.
- Moisture proof box.
- Convenient flip open cover, stainless steel coil and portable hanger.
- Use anywhere portable model - simply plug control into outlet and then the device into the control.
- Two stage model for two stages of heating and/or cooling or two speed fans.
- Single and two stage models: 16 Amp rating at 120V; 8 Amp rating at 240V.
- Portable model: 16 Amp rating at 120V.

KJ16110  
KT16110  
KP16110



KP16110  
(Portable  
Model)



## Higher Amp Rated SUNNE Thermostats

### Features

- Single stage thermostat for heating or cooling
- NEMA 4 enclosure
- Larger, easy read, 40 - 100° F dial
- Multi position mounting
- Higher amperage rating
- 16 amp rating @ 120 V & 12 amp rating @ 240 V
- Stainless steel coil

TF115



## Digital, Programmable RANCO Thermostats

### Features

- Single and two stage models
- Easy to read LCD display
- Programmable differential (1 to 30° F)
- Wide operating range (-30 to 220° F)
- NEMA 4 enclosure
- 8' temp probe included (extendable to 400')
- User selectable F/C°
- Lockout switch
- Two stage model for two stages of heating and/or cooling or two speed fans

T1NEMA4D1  
T2NEMA4D1



### Warranty

- 1 year warranty

**CANARM LTD. - Corporate Office**  
2157 Parkedale Ave., Brockville, ON  
Canada K6V 5V6  
Tel: (613) 342-5424 Fax: 1-800-263-4598

**CANARM LTD. - USA Warehouse**  
808 Commerce Park Drive  
Ogdensburg, New York, USA 13669  
Tel: 1-800-267-4427 Fax: 1-800-263-4598

**Arthur Manufacturing Facility**  
#7686 Concession 16, RR 4 Arthur, ON  
Canada N0G 1A0  
Tel: (519) 848-3910 Fax: (519) 848-3948  
E-Mail: [sales@bsmagri.com](mailto:sales@bsmagri.com)

Web Site: [www.canarm.com](http://www.canarm.com)  
E-Mail: [agsales@canarm.ca](mailto:agsales@canarm.ca)



## MSC-4

### Features

- One variable speed output (12.5 FLA)
- Minimum/maximum calibration
- ON/OFF switch
- May also be used as a light dimmer to power up to five, 250 Watt brooder lamps
- 115 or 230V AC operation



## MTC-4C



### Features

- One variable speed output (10 FLA)
- Two control knobs, one for adjusting temperature, one for adjusting idle speed
- An internal shunt for adjusting minimum ON/OFF speed
- Fixed 2°F off set-back for auto shut off
- 6°F differential temperature
- Extendable temperature sensor
- 115 or 230V AC operation

## FHC-1D

### Features

- One variable speed output (10 FLA)
- Heater Interlock Relay (10 FLA)
- Extendable temperature sensor
- Heat on at two degrees below temperature set point
- Temperatures displayed in Fahrenheit or Celsius
- Adjustable differential
- Adjustable idle
- Three second full-power turn-on minimizes fan motor ice-up
- 115 or 230V AC operation



## Warranty

- 2 year limited warranty

**CANARM LTD. - Corporate Office**  
 2157 Parkedale Ave., Brockville, ON  
 Canada K6V 5V6  
 Tel: (613) 342-5424 Fax: 1-800-263-4598

**CANARM LTD. - USA Warehouse**  
 808 Commerce Park Drive  
 Ogdensburg, New York, USA 13669  
 Tel: 1-800-267-4427 Fax: 1-800-263-4598  
 Web Site: [www.canarm.com](http://www.canarm.com)  
 E-Mail: [agsales@canarm.ca](mailto:agsales@canarm.ca)

**Arthur Manufacturing Facility**  
 #7686 Concession 16, RR 4 Arthur, ON  
 Canada NOG 1A0  
 Tel: (519) 848-3910 Fax: (519) 848-3948



# MANUAL VARIABLE SPEED CONTROL



**NEW!** Now Approved for use on SD Fans!

## MC CONTROL

### Features

- Minimum speed adjustment screw.
- Designed to fit a standard 3" x 5" electrical box.
- Mount in a dry location.
- Now available in 230V/1/60HZ

**NEW**

## Performance Data & Specifications

Model Number	Power Supply	Ampere Rating
MC-3	120V/1/60HZ	2.5
MC-5		5.0
MC-10		10.0
MC-15		15.0
MC-5-230	230V/1/60HZ	5.0

**NEW**

## Warranty

- 1 year limited warranty
- **Not for use on PLF/FG/PF/CA-AG/TF fans**



**CANARM LTD. - Corporate Office**  
 2157 Parkedale Ave., Brockville, ON  
 Canada K6V 5V6  
 Tel: (613) 342-5424 Fax: 1-800-263-4598

**CANARM LTD. - USA Warehouse**  
 808 Commerce Park Drive  
 Ogdensburg, New York, USA 13669  
 Tel: 1-800-267-4427 Fax: 1-800-263-4598  
 Web Site: [www.canarm.com](http://www.canarm.com)  
 E-Mail: [agsales@canarm.ca](mailto:agsales@canarm.ca)

**Arthur Manufacturing Facility**  
 #7686 Concession 16, RR 4 Arthur, ON  
 Canada N0G 1A0  
 Tel: (519) 848-3910 Fax: (519) 848-3948



## TVS

### Features

- Digital display of temperature, alarms, and settings
- Two independent variable speed stages (7.5 FLA each)
- One relay stage (6 FLA) Heat/Cool
- Seven factory program settings can be easily changed by the user
- Internal memory is retained during power failure
- Alarm relay to signal high or low temperature, power interruption, or low line voltage
- Extendable temperature sensor
- 115 or 230V AC operation



## SEC-HD

### Features

- Digital display of temperature, alarms, and settings
- Heavy duty relays
- Two variable speed stages (10 FLA each)
- Three stages that can be used for heating or cooling (6 FLA each)
- ON indicator lights for each stage
- Digital temperature display with four digit accuracy
- Internal memory retention during a power failure
- Alarm relay to signal high or low temperature, power interruption or low line voltage
- Extendable temperature sensor
- 115 or 230V AC operation



## PEC

### Features

- Digital display of temperature, alarms, and settings
- User configurable Growth Curve, can be set up to 315 days
- Two variable stages (7.5 FLA)
- Three fixed heat/cool stages (4.4 FLA @ 115 VAC or 2.2 FLA @ 230 VAC)
- High or low alarm contact for an external alarm
- Fixed stages can be used as duty cycle timers
- Can control an inlet actuator
- Stage 5 can operate as a proportional interval control
- Internal memory retention during a power failure
- Extendable temperature sensor
- Electrical rating: 115/230V AC



## Warranty

- 2 year limited warranty

**CANARM LTD. - Corporate Office**  
 2157 Parkedale Ave., Brockville, ON  
 Canada K6V 5V6  
 Tel: (613) 342-5424 Fax: 1-800-263-4598

**CANARM LTD. - USA Warehouse**  
 808 Commerce Park Drive  
 Ogdensburg, New York, USA 13669  
 Tel: 1-800-267-4427 Fax: 1-800-263-4598  
 Web Site: [www.canarm.com](http://www.canarm.com)  
 E-Mail: [agsales@canarm.ca](mailto:agsales@canarm.ca)

**Arthur Manufacturing Facility**  
 #7686 Concession 16, RR 4 Arthur, ON  
 Canada NOG 1A0  
 Tel: (519) 848-3910 Fax: (519) 848-3948



## P9500

### Features

The **Dwyer Mark II** series molded manometer has a curved inclined-vertical tube that provides higher ranges with easily read increments at low readings.

The manometer should be used in all static pressure ventilated buildings to insure proper inlet and fan coordination and sizing. Improper static pressure will result in poor ventilation and possible building or exhaust fan damage as well as poor livestock production.

The manometer should be used as an aid for setting up proportional inlet controls.



P9500 Mark II Manometer



## SM-18

### Features

*The unique pocket-knife design conveniently protects the unit when not in use. The skymate wind meter monitors the wind speed, temperatures and windchill. It is ideal for ventilation set up, monitoring and troubleshooting in Agricultural or HVAC Applications.*

- Optional units: knots, MPH, KPH, M/Sec, Ft/Min, Beaufort, Fahrenheit, Centigrade
- Operational modes: Current wind speed - average over 2 secs, Average wind speed - 5,10, or 13 secs, Maximum wind speed - 2 sec gust since power on
- Auto shutdown after 20 minutes
- CR2032 Lithium battery (included)
- 5.5" x 1.75" x .75" / 142x47x20mm (closed)

## TS-15

### Features

- Manual control for 2 speed fans
- High/low/off SPDT switch
- For dry locations



## S2907

### Features

- High/low Thermometer
- Inexpensive temperature monitoring
- Push button reset

## Warranty

- 2 year limited warranty

**CANARM LTD. - Corporate Office**  
2157 Parkedale Ave., Brockville, ON  
Canada K6V 5V6  
Tel: (613) 342-5424 Fax: 1-800-263-4598

**CANARM LTD. - USA Warehouse**  
808 Commerce Park Drive  
Ogdensburg, New York, USA 13669  
Tel: 1-800-267-4427 Fax: 1-800-263-4598  
Web Site: [www.canarm.com](http://www.canarm.com)  
E-Mail: [agsales@canarm.ca](mailto:agsales@canarm.ca)

**Arthur Manufacturing Facility**  
#7686 Concession 16, RR 4 Arthur, ON  
Canada NOG 1A0  
Tel: (519) 848-3910 Fax: (519) 848-3948