



CP - COMMERCIAL CEILING FAN

Ideally suited for circulating air in Industrial and Commercial Applications. Canarm's "CP" Fans help save energy year round.

FEATURES

- Available with 36", 48" and 56" blade sweeps.
- Variable speed motor (all motors are impedance protected, PSC type variable speed with permanently lubricated ball bearing motors).
- When used with our MC series speed controls the speed range is infinite.
- Painted steel blades with curved ends deliver maximum airflow over wide areas.
- All models are reversible (exception: CP56 c/w cord & plug is downdraft only).
- Reversible motor provides both winter destratification and summer time cooling.



Downrods available as accessories in 8" or 36" sizes. See next page.

Black now available in 36" and 48".

MODEL NUMBER	COLOR	AIRFLOW	FAN SIZE	MAX RPM	AIR VELOCITY 5' FROM FAN	AIR DELIVERY @ FLOOR	HIGH AMPS	LOW AMPS	HIGH WATTS	LOW WATTS	DOWNROD LENGTH	SHIPPING WEIGHT (LBS.)
CP36	White	Up/Downdraft	36"	380	750 ft/min	7,100 cfm	0.7	0.25	76	28	16"	12
NEW CP36BK	Black	Up/Downdraft	36"	380	750 ft/min	7,100 cfm	0.7	0.25	76	28	16"	12
CP48	White	Up/Downdraft	48"	320	700 ft/min	13,000 cfm	0.8	0.35	86	36	16"	16
NEW CP48BK	Black	Up/Downdraft	48"	320	700 ft/min	13,000 cfm	0.8	0.35	86	36	16"	16
CP56 F&R	White	Up/Downdraft	56"	310	660 ft/min	20,500 cfm	0.9	0.4	97	40	16"	17
CP56S (c/w 36" downrod)	White	Up/Downdraft	56"	310	660 ft/min	20,500 cfm	0.9	0.4	97	40	36"	19
CP56 C&P c/w cord & plug, non-reversible	White	Downdraft	56"	310	660 ft/min	20,500 cfm	0.9	0.4	97	40	16"	18
CP56 BR	Brown	Up/Downdraft	56"	310	660 ft/min	20,500 cfm	0.9	0.4	97	40	16"	17
CP56FRBK	Black	Up/Downdraft	56"	310	660 ft/min	20,500 cfm	0.9	0.4	97	40	16"	18
NEW CP56WH c/w Speed Control, Non reversible	White	Downdraft	56"	310	660 ft/min	20,500 cfm	0.9	0.4	97	40	16"	17



HPWP - HIGH PERFORMANCE CEILING FANS

Engineered and designed for general applications where above average area coverage and cooling velocity are required.

FEATURES

- Reversible motor for both winter destratification and summer time cooling
 - Fans are sealed and suitable for high moisture applications.
 - All high performance fans are weather resistant.
 - Straight blades and heavy duty motors for higher air movement and better cooling capacity.
- 36" downrod available as an accessory. See next page.

MODEL NUMBER	COLOR	AIRFLOW	FAN SIZE	MAX RPM	AIR VELOCITY 5' FROM FAN	AIR DELIVERY @ FLOOR	HIGH AMPS	HIGH WATTS	DOWNROD LENGTH	SHIPPING WEIGHT (LBS.)
CP48 HPWP	White	Up/downdraft	48"	325	700 ft/min	21,000 cfm	0.63	62	16"	18
CP56 HPWP	White	Up/downdraft	56"	319	660 ft/min	27,500 cfm	0.83	100	16"	24
CP60 HPWP	White	Up/downdraft	60"	292	650 ft/min	46,000 cfm	0.84	101	16"	25