





Ideally suited for circulating air in Industrial and Commercial Applications. Canarm's "CP" Fans help save energy year round.

## **FEATURES**

- · Available with 36", 48" and 56" blade sweeps.
- · Variable speed motor (all motors are impedance protected, PSC type variable speed with permanently lubricated ball bearing motors).
- · When used with our MC series speed controls the speed range is
- Painted steel blades with curved ends deliver maximum airflow over

Downrods available as accessories in 8" or 36" sizes. See next page.

- All models are reversible (exception: CP56 c/w cord & plug is downdraft only).
- Reversible motor provides both winter destratification and summer time cooling.



Black now available in 36" and 48".

| MODEL NUMBER                                  | COLOUR | AIRFLOW      | FAN<br>SIZE | MAX<br>RPM | AMPS<br>HIGH | LOW<br>AMPS | HIGH<br>WATTS | LOW<br>WATTS | VOLTS | DOWNROD<br>LENGTH | SHIPPING<br>WEIGHT (lbs) |
|---|--------|--------------|-------------|------------|--------------|-------------|---------------|--------------|-------|-------------------|--------------------------|
| CP36  | White  | Up/Downdraft | 36"         | 380        | 0.7          | 0.25        | 76            | 28           | 120V  | 16"               | 12                       |
| CP36BK  | Black  | Up/Downdraft | 36"         | 380        | 0.7          | 0.25        | 76            | 28           | 120V  | 16"               | 12                       |
| CP48  | White  | Up/Downdraft | 48"         | 320        | 8.0          | 0.35        | 86            | 36           | 120V  | 16"               | 16                       |
| CP48BK  | Black  | Up/Downdraft | 48"         | 320        | 8.0          | 0.35        | 86            | 36           | 120V  | 16"               | 16                       |
| CP56 F&R                                      | White  | Up/Downdraft | 56"         | 310        | 0.9          | 0.4         | 97            | 40           | 120V  | 16"               | 17                       |
| CP56S<br>(c/w 36" downrod)                    | White  | Up/Downdraft | 56"         | 310        | 0.9          | 0.4         | 97            | 40           | 120V  | 36"               | 19                       |
| CP56 C&P<br>(c/w cord & plug, non reversible) | White  | Downdraft    | 56"         | 310        | 0.9          | 0.4         | 97            | 40           | 120V  | 16"               | 18                       |
| CP56 BR                                       | Brown  | Up/Downdraft | 56"         | 310        | 0.9          | 0.4         | 97            | 40           | 120V  | 16"               | 17                       |
| CP56FRBK                                      | Black  | Up/Downdraft | 56"         | 310        | 0.9          | 0.4         | 97            | 40           | 120V  | 16"               | 18                       |
| CP56WH<br>(c/w speed control, non reversible) | White  | Downdraft    | 56"         | 310        | 0.9          | 0.4         | 97            | 40           | 120V  | 16"               | 17                       |



## **HPWP - HIGH PERFORMANCE CEILING FANS**

Engineered and designed for general applications where above average area coverage and cooling velocity are required.

## **FEATURES**

- · Reversible motor for both winter destratification and summer time cooling
- Fans are sealed and suitable for high moisture applications.
- All high performance fans are weather resistant.
- Straight blades and heavy duty motors for higher air movement and better cooling capacity.

36" downrod available as an accessory. See next page.

| MODEL     | FAN SIZE | MAX RPM | AMPS HIGH | WATTS<br>HIGH | VOLTS | DOWNROD<br>LENGTH | SHIPPING<br>WEIGHT (LBS) |
|-----------|----------|---------|-----------|---------------|-------|-------------------|--------------------------|
| CP48 HPWP | 48"      | 325     | 0.55      | 62            | 120V  | 16"               | 18 lbs                   |
| CP56 HPWP | 56"      | 319     | 0.83      | 100           | 120V  | 16"               | 24 lbs                   |
| CP60 HPWP | 60"      | 292     | 0.84      | 101           | 120V  | 16"               | 25 lbs                   |