

LED

3" Recessed Downlight

DL-3-6RR-WH-C

CANARM LTD.

PO Box 367, 2157 Parkedale Avenue, Brockville, Ontario K6V5V6
Tel: 613-342-5424 | Fax: 1-800-263-4598

2555 Rue Bernard Lefebvre, Laval, Quebec H7C 0A5
Tel: 1-450-665-2535 | Fax: 1-450-665-0910

808 Commerce Park Drive, Ogdensburg, New York, USA 13669
Tel: 1-800-267-4427 | Fax: 1-800-263-4598

www.canarm.com

General

Size of Fixture: 3.7" W x 3.7" H x 2.09" D
 Finish: white
 Acrylic lens
 IC Rated, Driverless, 120 Volt, 6W
 Lumens: 330 lumens thru the lens, Dimmable
 Beam spread: 120°
 Bulb Life: 50,000 hours
 CRI: 90
 Colour Temperature: 3000K
 Starting Minimum Temperature: -40°C
 Compatible dimmers: LEVITON #742-6672-HLW,
 LEVITON #722-6674-PDW, LUTRON #SCL-153PH-WH
 Recessed mounted, J-Box included
 Max.# of lamps per 150W dimmer: 25 pcs
 Cut-out template: 3 1/4"
 Available 24" rough in plate: IPLED-SR-C



Packaging

Colour Box: 5.28" x 4.02" x 2.83" (134 x 102 x 72mm)
 Colour box weight: 0.55 lbs
 Master box: 11.23" x 8.86" x 15.16" (285 x 225 x 385mm)
 Pieces per Master box: 20
 Master box weight: 11.02 lbs

Warranty & Safety Standards

Warranty: LED Module-Limited 5 year
 Fixture-Limited 1 year
 cETLus rated
 Energy Star Rated
 Suitable for wet locations
 Indoor/Outdoor enclosed use



WARNING: The use of this product can expose you to chemicals including Cadmium, which is known to the State of California to cause cancer, and Lead, which is known to the State of California to cause birth defects and/or other reproductive harm. For more information go to www.P65Warnings.ca.gov.

Prepared for
Contact
Date
Presented by
Remarks