

# LED

## 6" Recessed Downlight

### DL-6-15RR-BN-C

CANARM LTD.

PO Box 367, 2157 Parkedale Avenue, Brockville, Ontario K6V5V6  
Tel: 613-342-5424 | Fax: 1-800-263-4598

2555 Rue Bernard Lefebvre, Laval, Quebec H7C 0A5  
Tel: 1-450-665-2535 | Fax: 1-450-665-0910

808 Commerce Park Drive, Ogdensburg, New York, USA 13669  
Tel: 1-800-267-4427 | Fax: 1-800-263-4598

www.canarm.com

#### General

Size of Fixture: 7.20" W x 7.20" H x 2.09" D  
Finish: brushed nickel  
Acrylic lens  
IC Rated, Driverless, 120 Volt, 15W  
Lumens: 820 lumens thru the lens, Dimmable  
Beam spread: 120°  
Bulb Life: 50,000 hours  
CRI: 90  
Colour Temperature: 3000K  
Starting Minimum Temperature: -40°C  
Compatible dimmers: LEVITON #742-6672-HLW,  
LEVITON #722-6674-PDW, LUTRON #SCL-153PH-WH  
Recessed mounted, J-Box included  
Max.# of lamps per 150W dimmer: 10 pcs  
Cut-out template: 6 1/2"  
Available 24" rough in plate: IPLED-SR-C



#### Packaging

Colour box: 6.65" x 5.39" x 2.83" (224 x 192 x 72mm)  
Colour box weight: 1.32 lbs  
Master box: 13.98" x 11.61" x 15.16" (465 x 405 x 385mm)  
Pieces per Master box: 20  
Master box weight: 27.86 lbs

#### Warranty & Safety Standards

Warranty: LED Module-Limited 5 year  
Fixture-Limited 1 year  
cETLus rated  
Energy Star Rated  
Suitable for wet locations  
Indoor/Outdoor enclosed use



**WARNING:** The use of this product can expose you to chemicals including Cadmium, which is known to the State of California to cause cancer, and Lead, which is known to the State of California to cause birth defects and/or other reproductive harm. For more information go to [www.P65Warnings.ca.gov](http://www.P65Warnings.ca.gov).

<b>Prepared for</b>
<b>Contact</b>
<b>Date</b>
<b>Presented by</b>
<b>Remarks</b>