

# LED

## 6" Recessed Downlight

### DL-6-15RR-WH-C

**CANARM LTD.**

PO Box 367, 2157 Parkedale Avenue, Brockville, Ontario K6V5V6  
Tel: 613-342-5424 | Fax: 1-800-263-4598

2555 Rue Bernard Lefebvre, Laval, Quebec H7C 0A5  
Tel: 1-450-665-2535 | Fax: 1-450-665-0910

808 Commerce Park Drive, Ogdensburg, New York, USA 13669  
Tel: 1-800-267-4427 | Fax: 1-800-263-4598

[www.canarm.com](http://www.canarm.com)

#### General

Size of Fixture: 7.20" W x 7.20" H x 2.09" D  
 Finish: white  
 Acrylic lens  
 IC Rated, Driverless, 120 Volt, 15W  
 Lumens: 820 lumens thru the lens, Dimmable  
 Beam spread: 120°  
 Bulb Life: 50,000 hours  
 CRI: 90  
 Colour Temperature: 3000K  
 Starting Minimum Temperature: -40°C  
 Compatible dimmers: LEVITON #742-6672-HLW,  
 LEVITON #722-6674-PDW, LUTRON #SCL-153PH-WH  
 Recessed mounted, J-Box included  
 Max.# of lamps per 150W dimmer: 10 pcs  
 Cut-out template: 6 1/2"  
 Available 24" rough in plate: IPLED-SR-C



#### **Packaging**

Colour Carton: 6.65" x 5.39" x 2.83" (224 x 192 x 72mm)  
 Weight: 1.32 lbs  
 Master box: 13.98" x 11.61" x 15.16" (465 x 405 x 385mm)  
 Pieces per master: 20  
 Weight: 27.86 lbs

#### **Warranty & Safety Standards**

Warranty: LED Module-Limited 5 year  
 Fixture-Limited 1 year  
 cETLus rated  
 Energy Star Rated  
 Suitable for wet locations  
 Indoor/Outdoor enclosed use



**WARNING:** The use of this product can expose you to chemicals including Cadmium, which is known to the State of California to cause cancer, and Lead, which is known to the State of California to cause birth defects and/or other reproductive harm. For more information go to [www.P65Warnings.ca.gov](http://www.P65Warnings.ca.gov).

<b>Prepared for</b>
<b>Contact</b>
<b>Date</b>
<b>Presented by</b>
<b>Remarks</b>